

FAXCONT FC-220

Samsung Module Series Zoom Camera



Overview

- High Resolution Zoom Camera. (23X ~ 30X, Selectable)
- With B/W, Color Auto Exchange, Min. Illumination from 1 ~ 12 lx adjustable. (Selectable)
- Built-in OSD Display, Camera Parameter Setup.

Main Features

- Built-in control keypad, user can easily control camera zoom and focus ... etc.
- Various kinds of protocol to select. (FAXCONT®, Pelco P, Pelco D)
- Through keyboard controller to setup camera parameter.
- Built-in RS-485 port, executing commands to the camera by PC.
- Chinese / English preset title display.
- Built-in CDS, automatic or hand adjustment aperture, shutter, gain, brightness, expose and RGB color gain.
- Video timer display.
- At least six groups preset.
- Single image freeze function.
- Privacy area setup function. (Optional)

Order Information

- FC-606 Camera Housing
- FC-606 HB Camera Housing with Fan / Heater
- FC-607 Camera Housing
- FC-607 HB Camera Housing with Fan / Heater
- FC-607 IR Camera Housing
- FC-27W 7" Aluminum Dome Enclosure
- FC-27WN 7" Aluminum Dome Enclosure
- FC-29W 9" Dome Enclosure
- Includes DC 12V 1A Power Adaptor



FC-460I
Samsung SDM-231



FC-460J
Samsung SDM-330

Technical Specifications

Specifications / Model	FC-220I	FC-220IP	FC-220J	FC-220JP
Video Signal Format	NTSC	PAL	NTSC	PAL
Day / Night	Yes		Yes	
Image Sensor	1/4” Interline Transfer CCD		1/4” Vertical double density interline CCD	
Horizontal Resolution	520 TV lines			
Num. of Effective Pixels	App. 380,000	App. 440,000	App. 380,000	App. 440,000
Lens	23X Optical, f=3.84 ~ 88.4mm, F1.6 ~ 3.2		30X Optical, f=3.3 ~ 99mm, F1.6 ~ 3.2	
Digital Zoom	10X (230X with optical zoom)		8X (240X with optical zoom)	
Minimum Illumination	Color : 0.7 Lux/F1.6 (50 IRE) B/W : 0.1 Lux/F1.6 (50 IRE)		Color : 0.4 Lux/F1.6 (50 IRE) B/W : 0.08 Lux/F1.6 (50 IRE)	
Flicker Cancel	Auto	—	Auto	—
Privacy Zone Masking	Yes			
S/N ratio	More than 50 dB			
Data Transfer	RS-485			
Power Consumption	DC12V			